

540500 MS-MSP Article see - 0,00




## Connector rigid

Rigid line connector for overhead line pulling, for connection of different pull ropes, slim construction for easy running through the pulleys. These swivels are suitable for pulling over capstans or line tensioner.

kN = Minimum Breaking Load

Code	Type	D	L	Fork	Bolt	kN	kg
537010	FTS 28	28	59	11	17	70	0,14
537040	FTS 41	41	72	14	19	110	0,35
537080	FTS 48	48	90	19	20	160	0,53
537120	FTS 56	56	101	19	22	220	0,77
537170	FTS 60	60	120	26	27	360	1,05



## Overhead line swivels

Overhead line swivels, connection between pulling rope and pulling grip. With ball bearings, therefore only suitable to absolute twist-free steel ropes. Avoids untwisting the conductor. These swivels may not be used for pulling over capstans or line tensioner. For this please use above mentioned types FTS 28-60.

kN = Minimum Breaking Load

Code	Type	D	L	Fork	Bolt	kN	kg
537280	FVD 18	18	80	6,5	6	21	0,11
537300	FVD 25	25	109	9	10	45	0,30
537360	FVD 30	30	128	12	12	60	0,50
537410	FVD 35	35	137	12	14	90	0,70
537490	FVD 40	40	160	14	16	120	1,12
537550	FVD 50	55	187	18	16	165	1,90
537580	FVD 55	55	190	20	18	180	2,30
537640	FVD 60	60	220	23	20	225	3,10
537670	FVD 65	65	235	26	24	300	3,55
537700	FVD 75	75	270	30	27	320	6,70
537730	FVD 85	85	305	35	30	400	9,40
537760	FVD 100	100	340	38	36	500	14,30