



### AS120-2 - Battery operated hydraulic cutting tool

**Technical characteristics:**

- 3 years of warranty or 20.000 work cycles
- Light and compact structure
- Cutting head with snap closure, rotates 360°
- High speed feed with double hydraulic cylinder
- Pressure release button with single handed operation (on both sides, for left and right handed operators)
- Fastening ring for shoulder strap
- Ergonomic grip for weight balance to ensure an easy and safe operation
- Plastic housing, grip and pressure release button, insulating and shock resistant
- Powerful LED for working space illumination

Tool dimensions: ..... 359 x 639 x 91 mm  
 Tool weight (with battery): ..... 10,5 kg

Description	Order No.	Dimensions	Weight
Set cutting tool AS120-2	AS120-2	725 x 480 x 170mm	14,6 kg
Movable cutting blade	SMI120-2	-	1300 g
Knife guiding plate	MFI120-2	-	140 g

Accessories see page 209-212

**Set equipment:**

- Test report
- Battery-operated hydraulic cutting tool
- Battery 18 V/3,0 Ah Li-Ion (RA11)
- Battery charger (LG8)
- Rigid plastic case
- Shoulder strap (TG2)

4



Set AS120-2

SMI120-2



Spare blade and blade guide

MFI120-2

### CUTTING RANGE TABLE PS120-2 - AS120-2

Sector of use:		Tensile strength N/mm <sup>2</sup>	<math>\varnothing</math> 30 mm	<math>\varnothing</math> 35 mm	<math>\varnothing</math> 40 mm	<math>\varnothing</math> 45 mm	<math>\varnothing</math> 50 mm	<math>\varnothing</math> 55 mm	<math>\varnothing</math> 60 mm	<math>\varnothing</math> 65 mm	<math>\varnothing</math> 70 mm	<math>\varnothing</math> 75 mm	<math>\varnothing</math> 80 mm	<math>\varnothing</math> 85 mm	<math>\varnothing</math> 90 mm	<math>\varnothing</math> 95 mm	<math>\varnothing</math> 100 mm	<math>\varnothing</math> 105 mm	<math>\varnothing</math> 110 mm	<math>\varnothing</math> 115 mm	<math>\varnothing</math> 120 mm	<math>\varnothing</math> 125 mm
Copper	Cable		<math><410</math>																			
Aluminium	Cable	<math><210</math>																				